

### Features:

- Flat composite design with segmented bursting pattern
- Superior fatigue and cycle life when compared to flat single hinge designs
- Designed to be non-fragmenting
- Interchangeable with existing vent installations
- Materials: SST/TFE/SST
- Square, Rectangular, and Round configurations
- Burst ratings from 0.50 to 8.00 psi  
(Contact ZOOK for greater pressures)
- 0% Manufacturing range is standard
- CV vents have no moving parts, therefore are maintenance free
- Manufactured to mount into standard angle frames
- Custom sizes and materials available upon request

### Option:

- Gaskets



Operating Specifications	CV-II-F	CV-II-FS	CV-II-FSB
Max Operating Pressure <sup>1</sup>	60%	60%	60%
Max Vacuum Rating	50% of P <sub>stat</sub>	= to P <sub>stat</sub>	> P <sub>stat</sub>
Maximum Temperature	500°F (260°C)	500°F (260°C)	500°F (260°C)
Burst Pressure Tolerance	Relieving Pressure		Tolerance
	0.50 to 0.99 psi		±0.33 psi
	1.00 to 3.99 psi		±0.50 psi
	4.00 to 8.00 psi		±1.00 psi

<sup>1</sup>Calculation based on low end of burst pressure tolerance

<b>CV-II-F</b>	Design offers up to 100% venting area
<b>CV-II-FS</b>	Designed with integral support to withstand vacuum or back-pressure up to the static burst pressure of the vent panel
<b>CV-II-FSB</b>	Designed to be used with support bars in the inlet frame, used when vacuum or backpressure exceeds the static burst pressure of the vent panel

All ZOOK explosion vents are tested in accordance with the National Fire Protection Association standard NFPA 68 and meet the low mass per unit area requirement "The weight of the vent closure shall not exceed 2.5 lbs/sq. ft. of free vent area."

# Standard Vent Panel Sizes

## Square / Rectangular

Nominal Size		Relief Area*		Minimum Burst Pressure	
Inches	cm	sq. in.	sq. cm.	psig	bar
9 X 12	23 X 30	88	568	2.0	0.14
12 X 12	30 X 30	121	781	2.0	0.14
12 X 18	30 X 46	187	1206	1.5	0.10
12 X 24	30 X 61	253	1632	1.5	0.10
18 X 18	46 X 46	289	1865	1.0	0.07
18 X 24	46 X 61	391	2523	1.0	0.07
18 X 30	46 X 76	493	3181	1.0	0.07
18 X 35	46 X 89	578	3729	1.0	0.07
24 X 24	61 X 61	529	3413	1.0	0.07
24 X 30	61 X 76	667	4303	1.0	0.07
24 X 36	61 X 91	805	5194	0.5	0.03
24 X 44	61 X 112	989	6381	0.5	0.03
30 X 30	76 X 76	841	5426	0.5	0.03
30 X 36	76 X 91	1015	6548	0.5	0.03
30 X 40	76 X 102	1131	7297	0.5	0.03
30 X 44	76 X 112	1247	8045	0.5	0.03
36 X 36	91 X 91	1225	7903	0.5	0.03
36 X 44	91 X 112	1505	9710	0.5	0.03
44 X 44	112 X 112	1849	11929	0.5	0.03
44 X 69	112 X 175	2924	18864	0.5	0.03

## Round

Nominal Size (diameter)		Relief Area*		Minimum Burst Pressure	
Inches	cm	sq. in.	sq. cm.	psig	bar
8	20	38	248	3.0	0.21
10	25	64	410	2.5	0.17
12	30	95	613	2.0	0.14
14	36	133	856	1.5	0.10
16	41	177	1140	1.3	0.09
18	46	227	1464	1.0	0.07
20	51	284	1829	1.0	0.07
24	61	415	2680	1.0	0.07
30	76	661	4261	0.5	0.03
32	81	755	4869	0.5	0.03
36	91	962	6207	0.5	0.03
40	102	1195	7707	0.5	0.03
42	107	1320	8518	0.5	0.03
44	112	1452	9369	0.5	0.03

For larger sizes or sizes not shown, contact ZOOK.

\*Relief area is based on relieving area of CV-II-F type vent panel. Actual relief area will be reduced on other vent types or if support bars are used in inlet frame. Contact ZOOK for more information.



**ZOOK Enterprises, LLC**  
 16809 Park Circle Drive  
 Chagrin Falls, OH 44022 U.S.A.  
 Toll Free **800.543.1043**  
 Phone **440.543.1010**  
 Fax **440.543.4930**  
 E-mail **sales@zook.cc**

**ZOOK Canada, Inc.**  
 4400 South Service Road  
 Burlington, ON Can. L7L 5R8  
 Toll Free **800.370.6057**  
 Phone **905.681.2885**  
 Fax **905.681.8838**  
 E-mail **sales.canada@zook.cc**

**ZOOK Europe, LTD.**  
 Unit 1.14, Great House Waterside Business Park  
 Redwall Close, Rotherham Road  
 Dinnington, Sheffield UK. S25 3QA  
 Phone **0044 (0) 1909 560999**  
 Fax **0044 (0) 1909 560860**  
 E-mail **zookeurope@zook.cc**



**visit us on the web at [www.zook.cc](http://www.zook.cc)**